EVERSAFE
Working Safety

DATASHEET







LA40-AC

Heavy Duty Housing

Low Power Consumption

Long Life LED’s

Low Maintenance

Designed for Offshore Use


The LA series is a highly efficient and rugged LED light fixture for harsh offshore conditions.

The versatile design with four optical variations can be used for different applications such as work & walkway lights, ID sign lights, etc.

Utilizing low power to provide high output, the LA series is rugged and low maintenance.

Sabik Offshore GmbH reserves the right to change, without notice, the contents of this document. The information provided by Sabik Offshore GmbH is as accurate and reliable as practicably possible at the date of publication, however, no responsibility is assumed by Sabik Offshore GmbH for its use and correctness. © Sabik Offshore GmbH 2021.

Dimensions & Weight







Height	85 mm
Width	156 mm
Length	417 mm
Weight	2,6 kg

Material

Housing / Profile	Extruded Seawater resistant anodized aluminum
End lid	Stainless steel 316 L / 1.4404
Gasket	TPE-K UV-AD2 TC5MUZ
Glass	UV resistant clear polycarbonate

Sabik Offshore GmbH reserves the right to change, without notice, the contents of this document. The information provided by Sabik Offshore GmbH is as accurate and reliable as practicably possible at the date of publication, however, no responsibility is assumed by Sabik Offshore GmbH for its use and correctness. © Sabik Offshore GmbH 2021.


Optical System

Variant		Wide	Extra Wide	Narrow	Asymmetric
Product ID		LA40-AC W	LA40-AC XW	LA40-AC N	LA40-AC AS
Lumen	15 W, 40%	500 lm	600 lm	680 lm	560 lm
	22 W, 70%	880 lm	1050 lm	1190 lm	980 lm
	30 W, 100%	1260 lm	1500 lm	1700 lm	1400 lm
Color Temperature		4000 K	4000 K	4000 K	4000 K
Color Rendering Index (CRI)					
Risk group (acc. to EN 61471:2008)		RG1	RG1	RG1	RG1
Optical Profile					

Note: blue = horizontal distribution; red = vertical distribution

Electrical Connection


Type	Operating Voltage	Power cons.	Connection
LA40-AC	AC 200-240 V – 50/60 Hz	30 W	Live-L, Neu.-N, Y/G-PE




* Max. 5 units on 16 A circuit breaker at 230 V AC

Sabik Offshore GmbH reserves the right to change, without notice, the contents of this document. The information provided by Sabik Offshore GmbH is as accurate and reliable as practicably possible at the date of publication, however, no responsibility is assumed by Sabik Offshore GmbH for its use and correctness. © Sabik Offshore GmbH 2021.


Dimming Options



30 W, 100%




22 W, 70%



15 W, 40%


Components

1. Front Glass
2. Gasket for Front Glass
3. LED Board
4. Earthing
5. End Cap
6. Light Engine
7. Cable Gland
8. Housing



	Size	For cable diameter	Key width
EMC Cable Gland	M20 x 1.5	8.0 – 15.0 mm	24 mm

Sabik Offshore GmbH reserves the right to change, without notice, the contents of this document. The information provided by Sabik Offshore GmbH is as accurate and reliable as practicably possible at the date of publication, however, no responsibility is assumed by Sabik Offshore GmbH for its use and correctness. © Sabik Offshore GmbH 2021.



1.	Electrical Connection
2.	Driver
3.	Dimming Option

Environmental Conditions

Ambient temperature (operation)	-25 ... +55 °C
Ambient temperature (storage / transport)	-25 ... +70 °C
Humidity (operation / storage / transport)	95% r.h. up to 45°C 70% r.h. for T > 45°C
Atmospheric pressure (operation / storage / transport)	80 ... 108 kPa
Degree of protection (acc. To IEC 60529)	IP66 & IP67
Luminaire classification (acc. to EN 60598-1:2018)	Rough service luminaire

Electrical Safety & Health

Protection class	Class I
Overvoltage protection	Class III
Pollution degree	3

Sabik Offshore GmbH reserves the right to change, without notice, the contents of this document. The information provided by Sabik Offshore GmbH is as accurate and reliable as practicably possible at the date of publication, however, no responsibility is assumed by Sabik Offshore GmbH for its use and correctness. © Sabik Offshore GmbH 2021.

Compliance

Electromagnetic Compatibility	EN 60945:2002, category “exposed” EN 61547:2009 EN 61000-6-2:2005 EN 61000-6-4:2007 + A1:2011
Environmental	EN 60945:2002, category “exposed” EN 60598-1:2015 + A1:2008 IEC 61892-1:2019
Product Safety	EN 60598-1:2015 + A1:2018 EN 60598-2-1:1989
Health	EN 62471:2008
Mechanical	EN 60945:2002, category “exposed” EN 60598-1:2015 + A1:2018 IEC 61892-1:2019 IEC 61892-3:2019

Reliability

Minimum LED lifetime	60 000 h

Ordering Information

Item Number	Product ID	Variant	Optic
30712100	LA40-AC	XW	Extra Wide
30712101	LA40-AC	W	Wide
30712102	LA40-AC	N	Narrow
30712103	LA40-AC	AS	Asymmetric

Sabik Offshore GmbH reserves the right to change, without notice, the contents of this document. The information provided by Sabik Offshore GmbH is as accurate and reliable as practicably possible at the date of publication, however, no responsibility is assumed by Sabik Offshore GmbH for its use and correctness. © Sabik Offshore GmbH 2021.